

CASH® Small Animal Tool

Non-penetrating captive bolt stunner

Cylindrical shaped cartridge powered humane stunning tool with non-penetrating concussion head suitable for poultry and other small animals



Why the **CASH®** Small Animal Tool!

- Trigger fired operation
- Lightweight and well balanced
- Automatic bolt return
- Robust construction
- Reliable performance
- Easy to learn and operate
- Low maintenance costs
- Proof tested in accordance with C.I.P.
- CE compliant to Machinery Directive 2006/42/EC
- Supplied with cleaning tools and maintenance instructions



Choice of two concussion heads



CASH® Small Animal Tool range

Description	Calibre	Product weight	Max cartridge	Product code
CASH® Small Animal Tool .22	.22"	1.5 kg	1 grain	CPK200

CASH® Small Animal Tool cartridge range

Calibre	Colour	Grain	Energy (J)	Suggested uses	Product code	
					Tin 50	Box 1000
.22"	Brown	1	76	Small animals and poultry	7505T	7505

Every Frontmatec Accles & Shelvoke stunning tool is provided with a range of support

- Cleaning and Maintenance tools
- Readily available spare parts service
- Regulatory requirement compliant user instructions
- Full maintenance instructions
- Downloadable online information such as manuals, cartridge selection guides, training videos etc.
- On-site and in-house maintenance support (dependent upon your supplier)

Other tools in the CASH® captive bolt stunners range



CASH®
Special



CASH®
Special Concussion



CASH®
Special XL



CASH®
Cowpuncher



CASH®
Magnum FreeFlight



CASH®
Magnum Auto



CASH®
Magnum Concussion



CASH®
Magnum XL

Contact

CN: shanghai@frontmatec.com
Phone: +86 215 859 4850

DK: kolding@frontmatec.com
Phone: +45 763 427 00

ES: sallent@frontmatec.com
Phone: +34 938 380 835

UK: birmingham@frontmatec.com
Phone: +44 121 313 3564

frontmatec.com
acclesandshelvoke.co.uk

DE: beckum@frontmatec.com
Phone: +49 252 185 070

NL: borculo@frontmatec.com
Phone: +31 545 259 999

RU: moscow@frontmatec.com
Phone: +7 495 424 9559

US: kansascity@frontmatec.com
Phone: +1 816 891 2440

